



#210.02

Gas Vapor Probe Kits with Dedicated Tips

Part #	Item
209.19	GVP Kit without drill
210.00	GVP Kit with DeWalt D25600K Hammer Drill
209.84	GVP Kit w/ Bosch 11245EVS Rotary Hammer Drill

Gas Vapor Probe Kits with Dedicated and Retract-A-Tip

Part #	Item
209.16	GVP Kit without drill
210.02	GVP Kit with DeWalt D25600K Hammer Drill
209.86	GVP Kit with Bosch 11245EVS Hammer Drill

GVP Kit Replacement Parts

Part #	Item
209.00	GVP Instruction DVD Video
209.01	AMS GVP Manual
211.00	Gas Vapor Tip & Umbrella
211.05	Removal Jack
214.045	Extension Drive Adapter to 3/4" ID
214.05	5/8" NF 4' Gas Vapor Probe Extension
214.06	5/8" NF 3' Gas Vapor Probe Extension
214.09	5/8" NF Gas Vapor Probe Tip Drive End
214.105	Slide Hammer Adapter to 3/4" OD
214.18	SDS-Max Drill Adapter to 3/4" OD
214.22	1 1/2" Concrete Bit SDS-Max
215.00	3/16" ID x 1/4" OD x 250' Fluoropolymer Tubing
215.06	Hand Pump
401.26	10" Cross Handle
400.99	5/8" NC Regular Slide Hammer
403.08	5/8" NF 4' Tile Probe Extension
403.10	5/8" x 3' Extendable Tile Probe Complete (with tile probe, tile probe tip, 5/8" NC to 5/8" NF adapter, and 10" rubber-gripped handle)
403.11	5/8" NF 3' Tile Probe Extension
403.13	5/8" NF Extendable Tile Probe Tip
405.27	5/8" NC Male to Splined Drill Adapter
427.20	5/8" NF Extendable Tile Probe Coupling
430.01	AMS Deluxe Carrying Case 1750

*Note: GVP kits use both 5/8in national coarse (NC) and national fine (NF) threaded connections.

Gas Vapor Probe Kits

AMS GVP kits are excellent for monitoring and sampling hydrocarbon spill sites, underground storage tanks, and around pipelines! They use a slide hammer or an electric rotary drive hammer drill and GVP drive extensions to insert a stainless steel GVP tip to the desired sampling depth. Fluoropolymer tubing is attached to a barb fitting on the GVP tip for remote sampling from the surface. Two GVP tips are available for use with GVP kits – dedicated tips and the AMS Retract-A-Tip. The kits include ten dedicated tips with umbrellas, and some kits also include the Retract-A-Tip. Each kit also comes with a 1 1/2" wild bore concrete bit, tip drive end, four 3' GVP extensions, 3' extendable tile probe complete, three 3' tile probe extension, 3/4" ID external drive adapter, SDS-Max drill adapter, SDS-Max 1 1/2" carbide bit, slide hammer, handle/hammer adapter, hand pump, 3/16" ID x 1/4" OD x 250' fluoropolymer tubing, removal jack, AMS deluxe carrying case, GVP manual, and instruction DVD.



#210.00
Use dedicated GVP tips or the AMS Retract-A-Tip.