



## PROACTIVE® 12 VOLT STAINLESS STEEL PUMP LINE

# Welcome to Proactive Environmental Products® 12 Volt Stainless Steel Pump Line

Celebrating 25 years manufacturing groundwater sampling equipment Proactive Environmental Products® understands your need for reliable, accurate, field-efficient groundwater pump systems and supplies. Our 12 volt Stainless Steel Pump Line offers improved time efficiency, greater sample accuracy, and makes for a more enjoyable groundwater sampling and monitoring experience. *This is our promise to you!*

### ABOUT THE 12 VOLT PROACTIVE® STAINLESS STEEL PUMP LINE

Applications: Portable use for purging, well development, low flow sampling and remediation

#### Features:

- Rugged, simple to use and lightweight
- NO compressed air canisters, bladders, air compressors or gas generators needed
- Battery operated: Powered by a 12 volt DC vehicle, AGM, or Deep Cycle Marine battery.  
(Please inquire for the best suitable portable battery for your pump system)
- All Proactive® 12 volt stainless steel portable pump systems are EPA low flow sampling compliant
- Control pump flow rate as low as 40-100 mL/s per minute
- To get lower flow rate than 40-100 mL/s per minute consider using our low flow valve in conjunction with the controller (NOTE: Do not valve pump without use of appropriate controller)
- Eliminate down-time in the field! Quick-change motor module in less than 60 seconds and your pump is ready for more field work
- Optional back-flow prevention. Ask about our Stainless Steel Non-Return Check Valve
- Easiest stainless steel pump system on the market to clean and maintain! Guaranteed!

#### Engineering and Design:

- Proactive® Low Flow with Power Booster XL LCD controllers are required with this pump line
- Computer engineered bottom debris filter screen allows operation under harsh conditions with higher turbidity
- Pump head, motor module, and components touching liquid are manufactured using 100% virgin stainless steel
- Simple counter-clockwise twist to remove the stainless steel outer casing for cleaning
- Each pump comes field-ready with wire, controller connector installed on a light-weight rugged steel locking reel with pump holster (designed to protect the pump while not in use)
- Also includes one additional back up motor module, a low flow valve, and a Proactive® dual purpose wrench
- Sleek dome-shape pump head minimizes well hang-ups
- Auto-priming and field ready right from the box (no priming needed, ever)
- Can run continuously in water without the need for a cool down! (not recommended for 24+ hour pump test – please inquire for pumps that are designed for 24+ hour pump tests)

Specifications may change without notice

**Tips** *Maximize the life of your pump: Clean your pump after every use and apply SS hose clamp on tube and pump discharge!  
Eliminate down-time: Keep a DC volt meter with your 12 volt pumps and pump systems!*

Stainless Steel Pump Line Page 2



# 12 Volt Stainless Steel

Portable Pump Line



The most reliable, easy-to-use 12 Volt Stainless Steel Pump Line!  
Easily fits into 2" and larger diameter wells

## Stainless Steel Monsoon® XL Pump

**lift: 120 feet\***  
**37 meters\***

Item: PS-10400



## Stainless Steel Hurricane® XL Pump

**lift: 150 feet\***  
**46 meters\***

Item: PS-10415



## Stainless Steel Mega-Monsoon® XL Pump

**lift: 170 feet\***  
**52 meters\***

Item: PS-10420



### Low Flow with Power Booster 2 XL LCD Controller Required Use With: SS Monsoon® XL Pump

Item: PA-10670



### Low Flow with Power Booster 2.5 XL LCD Controller Required Use With: SS Hurricane® XL Pump

Item: PA-10675



### Low Flow with Power Booster 3 XL LCD Controller Required Use With: SS Mega Monsoon® XL Pump

Item: PA-10680



### SS Monsoon® XL Motor Module

Required Use With:  
SS Monsoon® XL Pump

Item: PA-14060



### SS Hurricane® XL Motor Module

Required Use With:  
SS Hurricane® XL Pump

Item: PA-14065



### SS Mega Monsoon® XL Motor Module

Required Use With:  
SS Mega Monsoon® XL Pump

Item: PA-14070



Specifications may change without notice

\*Depth to Water (DTW)

EPA low flow sampling compliant: Proactive Environmental Products® Stainless Steel Pump Line can achieve 10 mL/s per minute

Stainless Steel Pump Line Page 3

WWW.PROACTIVEDIRECT.BIZ  
JAY@PROACTIVEDIRECT.BIZ



TOLL FREE PHONE: 1.877.99.HYDRO Ext. 101  
(49376)  
LOCAL PHONE: 1.941.243.3930

# 12 Volt Stainless Steel

Portable Pump Line



## Proactive® 12 Volt Stainless Steel Portable Pump Line Accessories

Customers Who Purchase Proactive Environmental Products® Stainless Steel Pump Line Also Purchase

### FULLY STOCKED TUBING WAREHOUSE!

3/8" x 1/2" od Tubing: 100' and 500' spools;  
PVC, Low Density Polyethylene,  
High Density Polyethylene, FEP  
(Teflon®) lined Polyethylene tubing



### PROACTIVE® STAINLESS STEEL NON RETURN CHECK VALVE



### PROACTIVE® SS DROP-TUBE AND WEIGHT COMBO

(enables the pump to lift at deeper well depths)

### HydroLine™ 800cm .45 InLine Micron Filter

When Metals Matter  
Why take a chance  
with your samples?

**HydroLine®**

300cm<sup>2</sup>, 600cm<sup>2</sup> & 800cm<sup>2</sup>  
.45 InLine Micron Filters



Ensuring the highest quality filters with  
responsible tracking by batch guaranteed!  
Options for low, medium, medium-high  
and high turbidity capacity .45 filters

### PROACTIVE® LOW FLOW VALVE



Specifications may change without notice

**Tips** Maximize the life of your pump: Clean your pump after every use and apply SS hose clamp on tube and pump discharge!  
Eliminate down-time: Keep a DC volt meter with your 12 volt pumps and pump systems!

EPA low flow sampling compliant: Proactive Environmental Products® Stainless Steel Pump Line can achieve 10 mL/s per minute

Stainless Steel Pump Line Page 4

WWW.PROACTIVEDIRECT.BIZ  
JAY@PROACTIVEDIRECT.BIZ



TOLL FREE PHONE: 1.877.99.HYDRO Ext. 101  
(49376)  
LOCAL PHONE: 1.941.243.3930



# 12 Volt Stainless Steel Portable Pump Line



The most reliable, easy-to-use 12 Volt Stainless Steel Pump Line!  
Easily fits into 2" and larger diameter wells

## Stainless Steel Monsoon<sup>®</sup> XL Pump

Lifts up to 120 feet\* (37 meters\*)

Required: **Low Flow with Power Booster 2 XL LCD Controller**

Powered by a 12 volt DC vehicle, AGM, or Deep Cycle Marine battery. Engineered for low flow sampling, purging and well development.

Pump Comes With:

- One installed motor module, a replacement motor module, (comes with motor module 'o' rings and Vitamin D oil for 'o' rings), a low flow valve, and Proactive<sup>®</sup> pump wrench
- Wire installed on pump and locking steel reel
- Holster installed on the reel to safely port the pump

### Field-Ready / Auto-Primed



Item: PS-10400

**Only  
24 pounds**

PUMPING DEPTH	GALLONS PER MINUTE
10	3.50
20	3.25
30	3.25
40	3.00
60	2.75
70	2.25
80	2.25
100	1.75
110	1.50
120	1.25

STAINLESS STEEL MONSOON <sup>®</sup> XL PUMP SPECIFICATIONS	
• DC Volt recommendation: 12-15 DC (direct current) at source	
• AMP Consumption (Max): 32 AMPS	
• Watt Consumption: 480 watts (max)	
• Measurements: Length 7.5" / Diameter 1.82"	
• Stainless steel eye hook on pump head for easy deployment and raising of the pump	
• Outer pump casing and motor module constructed from virgin Stainless Steel	
• Liquid does not come in contact with internal motor module components providing an effective and time - efficient pump cleaning	
• Comes with 130 feet of 12 gauge PVC coated wire installed on pump and reel	
• Required tubing: 3/8" ID Poly tubing can be used	

This pump is engineered to be dedicated in liquid 24 hours a day.  
Specifications may change without notice

\* Depth to Water (DTW)

## Low Flow with Power Booster 2 XL LCD Controller

Item: PA-10670

- Required with Stainless Steel Monsoon<sup>®</sup> XL Pump
- EPA Low Flow Sampling Compliant (flow rate as low as 10 mL/s per minute)
- Heavy Duty Reinforced Plastic Controller
- Ramp-up Control Dial
- Easy To Read LCD For Precise Control
- LVD- Low Voltage Disconnect
- Internal Cooling Fan
- Constant Voltage Boosting Technology (CVBT allows correct voltage to reach the pump)



**Only  
6 pounds**

**Tips** Maximize the life of your pump: Clean your pump after every use and apply SS hose clamp on tube and pump discharge!  
Eliminate down-time: Keep a DC volt meter with your 12 volt pumps and pump systems!

EPA low flow sampling compliant: Proactive Environmental Products<sup>®</sup> Stainless Steel Pump Line can achieve 10 mL/s per minute



# 12 Volt Stainless Steel Portable Pump Line



The most reliable, easy-to-use 12 Volt Stainless Steel Pump Line!  
Easily fits into 2" and larger diameter wells

## Stainless Steel Hurricane® XL Pump

Lifts up to 150 feet\* (46 meters\*)

Required: **Low Flow with Power Booster 2.5 XL LCD Controller**

Powered by a 12 volt DC vehicle, AGM, or Deep Cycle Marine battery. Engineered for low flow sampling, purging and well development.

Pump Comes With:

- One installed motor module, a replacement motor module, (comes with motor module 'o' rings and Vitamin D oil for 'o' rings), a low flow valve, and Proactive® pump wrench
- Wire installed on pump and locking steel reel
- Holster installed on the reel to safely port the pump

### Field-Ready / Auto-Primed



Item: PS-10415

**Only  
31 pounds**

PUMPING DEPTH	GALLONS PER MINUTE
10	3.75
20	3.75
30	3.50
40	3.25
60	3.00
70	2.75
80	2.50
100	2.00
110	1.75
120	1.50
130	1.50
150	0.75

### STAINLESS STEEL HURRICANE® XL PUMP SPECIFICATIONS

- DC Volt recommendation: 12-15 DC (direct current) at source
- AMP Consumption (max): 36 AMPS
- Watt consumption (max): 540 watts (max)
- Measurements: Length 7.5" / Diameter 1.82"
- Stainless steel eye hook on pump head for easy deployment and raising of the pump
- Outer pump casing and motor module constructed from virgin Stainless Steel
- Liquid does not come in contact with internal motor module components providing an effective and time - efficient pump cleaning
- Comes with 160 feet of 10 gauge PVC coated wire installed on pump and reel
- Required tubing: 3/8" ID Poly tubing can be used

This pump is engineered to be dedicated in liquid 24 hours a day.  
Specifications may change without notice

\* Depth to Water (DTW)

## Low Flow with Power Booster 2.5 XL LCD Controller

- Required with Stainless Steel Hurricane® XL Pump
- EPA Low Flow Sampling Compliant (flow rate as low as 10 mL/s per minute)
- Heavy Duty Reinforced Plastic Controller
- Ramp-up Control Dial
- Easy To Read LCD For Precise Control
- LVD- Low Voltage Disconnect
- Internal Cooling Fan
- Constant Voltage Boosting Technology (CVBT allows correct voltage to reach the pump)



Item: PA-10675

**Only  
6 pounds**

**Tips** Maximize the life of your pump: Clean your pump after every use and apply SS hose clamp on tube and pump discharge!

Eliminate down-time: Keep a DC volt meter with your 12 volt pumps and pump systems!

EPA low flow sampling compliant: Proactive Environmental Products® Stainless Steel Pump Line can achieve 10 mL/s per minute

WWW.PROACTIVEDIRECT.BIZ  
JAY@PROACTIVEDIRECT.BIZ



TOLL FREE PHONE: 1.877.99.HYDRO Ext. 101  
(49376)  
LOCAL PHONE: 1.941.243.3930

Stainless Steel Pump Line Page 6



# 12 Volt Stainless Steel Portable Pump Line



The most reliable, easy-to-use 12 Volt Stainless Steel Pump Line!  
Easily fits into 2" and larger diameter wells

## Stainless Steel Mega-Monsoon® XL Pump

Lifts up to 170 feet\* (52 meters\*)

Required: **Low Flow with Power Booster 3 XL LCD Controller**

Powered by a 12 volt DC vehicle, AGM, or Deep Cycle Marine battery. Engineered for low flow sampling, purging and well development.

Pump Comes With:

- One installed motor module, a replacement motor module, (comes with motor module 'o' rings and Vitamin D oil for 'o' rings), a low flow valve, and Proactive® pump wrench
- Wire installed on pump and locking steel reel
- Holster installed on the reel to safely port the pump



Item: PS-10420

Only  
34 pounds

### Field-Ready / Auto-Primed

PUMPING DEPTH	GALLONS PER MINUTE
10	3.25
20	3.00
40	3.00
50	2.75
70	2.50
80	2.25
90	2.25
100	2.00
120	1.75
140	1.25
150	1.00
170	0.25

### STAINLESS STEEL MEGA-MONSOON® XL PUMP SPECIFICATIONS

- DC Volt recommendation: 12 -15 DC (direct current) at source
- AMP consumption (max): 39 AMPS
- Watt consumption (max): 585 watts (max)
- Measurements: Length 7.5" / Diameter 1.82"
- Stainless steel eye hook on pump head for easy deployment and raising of the pump
- Outer pump casing and motor module constructed from virgin Stainless Steel
- Liquid does not come in contact with internal motor module components providing an effective and time - efficient pump cleaning
- Comes with 180 feet of 10 gauge PVC coated wire installed on pump and reel
- Required tubing: 3/8" ID Poly tubing can be used

This pump is engineered to be dedicated in liquid 24 hours a day.  
Specifications may change without notice

\* Depth to Water (DTW)

## Low Flow with Power Booster 3 XL LCD Controller

- Required with Stainless Steel Mega-Monsoon® XL Pump
- EPA Low Flow Sampling Compliant (flow rate as low as 10 mL/s per minute)
- Heavy Duty Reinforced Plastic Controller
- Ramp-up Control Dial
- Easy To Read LCD For Precise Control
- LVD- Low Voltage Disconnect
- Internal Cooling Fan
- Constant Voltage Boosting Technology (CVBT allows correct voltage to reach the pump)



Item: PA-10680

Only  
6 pounds

**Tips** Maximize the life of your pump: Clean your pump after every use and apply SS hose clamp on tube and pump discharge!

Eliminate down-time: Keep a DC volt meter with your 12 volt pumps and pump systems!

EPA low flow sampling compliant: Proactive Environmental Products® Stainless Steel Pump Line can achieve 10 mL/s per minute

Stainless Steel Pump Line Page 7

WWW.PROACTIVEDIRECT.BIZ  
JAY@PROACTIVEDIRECT.BIZ



TOLL FREE PHONE: 1.877.99.HYDRO Ext. 101  
(49376)  
LOCAL PHONE: 1.941.243.3930


# 12 Volt Stainless Steel

Portable Pump Line



The most reliable, easy-to-use 12 Volt Stainless Steel Pump Line!  
Easily fits into 2" and larger diameter wells

## Proactive® 12 Volt Stainless Steel Pumps



## Field-Ready / Auto-Primed

**Tips** Maximize the life of your pump: Clean your pump after every use and apply SS hose clamp on tube and pump discharge!  
Reduce stress on the wire: Apply stainless steel hose clamp on tube and pump discharge! And / Or use the stainless steel eye hook on the top of the pump designed for ss suspension cable!

Specifications may change without notice

EPA low flow sampling compliant: Proactive Environmental Products® Stainless Steel Pump Line can achieve 10 mL/s per minute

WWW.PROACTIVEDIRECT.BIZ  
JAY@PROACTIVEDIRECT.BIZ



Stainless Steel Pump Line Page 8  
TOLL FREE PHONE: 1.877.99.HYDRO Ext. 101  
(49376)  
LOCAL PHONE: 1.941.243.3930



# 12 Volt Stainless Steel

Portable Pump Line



The most reliable, easy-to-use 12 Volt Stainless Steel Pump Line!  
Easily fits into 2" and larger diameter wells

## Proactive® Stainless Steel Pump Controllers



### Features:

- Provides wide range of options from high purge to low flow sampling with the turn of a knob
- EPA Low Flow Sampling compliant
- Light weight (6 pounds) and compact in size
- LCD read out reflects voltage range reflecting consistent flow rate
- Powered by a 12 volt DC vehicle, AGM, or Deep Cycle Marine battery. Engineered for low flow sampling, purging (Please inquire for the best suitable portable battery for your pump system)

### Engineering and Design:

- Heavy duty reinforced plastic case
- Easy to read LCD for precise control
- Low Voltage Disconnect (LVD) at 10.75 volts (turns off pump system)
- Constant Voltage Boosting Technology (CVBT) allows the correct voltage to reach the pump motors
- 'Ramp Up' control dial
- 7 foot wire lead to battery clamps and 8 foot wire leads to pump connector
- 6 month parts and labor warranty

Specifications may change without notice

**Tips** Maximize the life of your pump: Clean your pump after every use and apply SS hose clamp on tube and pump discharge!

Eliminate down-time: Keep a DC volt meter with your 12 volt pumps and pump systems!

EPA low flow sampling compliant: Proactive Environmental Products® Stainless Steel Pump Line can achieve 10 mL/s per minute

Stainless Steel Pump Line Page 9

WWW.PROACTIVEDIRECT.BIZ  
JAY@PROACTIVEDIRECT.BIZ



TOLL FREE PHONE: 1.877.99.HYDRO Ext. 101  
(49376)  
LOCAL PHONE: 1.941.243.3930