


# Sentek Solo

'proven quality, enduring value'



Sentek Solo is a cost effective, continuous soil moisture and salinity monitoring solution. The Sentek Solo system consists of a battery powered EnviroSCAN or EasyAG probe connected to a Solo Head Unit. Data is accessed in-field via the robust SoloPORTER or a notebook computer, and displayed in Sentek's Irrimax software.

## Sentek Solo Probe Options

- Available with both EasyAG and EnviroSCAN probes
- Includes logging, Sentek Solo RS232 interface for on-probe data storage
- Utilises same interface as Sentek Plus, allowing for simple upgrade to wireless, web compatible communications



## Sentek Solo Head Unit

- One Sentek Solo Head Unit required per probe
- Sentek Solo Head Unit is connected to the probe via 3 metres of cable
- Powered by 4 removable alkaline AA batteries
- Robust download port for in-field downloading

## Download Options

Data downloaded into Sentek's Irrimax software via:

- SoloPORTER or;
- Download cable to notebook computer

## SoloPORTER

- Durable and light weight design
- Download and battery power indicator lights
- One device downloads data from multiple probes
- Data storage on USB flash drive
- Transfer data from USB flash drive direct to desktop computer for viewing in Irrimax Software



Diviner 2000 • EnviroSCAN • EasyAG • TriSCAN • SentekPlus • SentekRT6 • SentekSolo • Irrimax • Sentek SoluSAMPLER

Your local distributor is:

**Sentek sensor**

technologies

www.sentek.com.au

© copyright 2010