

DOCUMENT #W133-01





Parameters:

pH units Temperature °C mV/ORP/Redox (oxidation reduction potential) mV



EcoSense® pH100M pH/ORP/mV/Temperature

Accurate, economical, handheld instrument

The YSI EcoSense[®] instruments provide accurate data in the most affordable format. The "M" stands for memory and the instruments feature a real-time clock, larger memory and simple data transfer to a PC with a built-in USB port.

The pH100M is easy-to-use, field-worthy and provides accurate and repeatable measurements.

The pH100M measures pH, mV/ORP and temperature with the following features:

- Rugged, waterproof, field-worthy case. IP-67 rated.
- Waterproof micro-USB port for transferring data to PC; no software required.
- Holds 250 data sets; no need to write down data.
- Real-time clock for date/time stamp of saved data.
- User-selectable re-calibration prompt provides reminder to calibrate.
- Automatic buffer recognition (US or NIST buffer sets).
- Automatic or manual temperature compensation.
- 1-year instrument warranty; 6-month electrode warranty.
- 1 and 4-meter field cables available; lab pH and ORP electrodes available.
- Displays electrode efficiency.
- Autolock mode holds stable readings on display.

The pH100M is designed for quick, accurate measurements in an economical platform. Easy-to-use, waterproof and backed by a 1-year warranty, the pH100M is ideal for a wide range of applications.

YSI.com/pH100M

EcoSense pH100M Instrument Only Specifications

Temperature	Range	-10 to 120°C
	Resolution	0.1°C
	Accuracy	<u>+</u> 0.3°C (System accuracy - instrument, sensor, cable)
рН	Range	-2 to 16 units
	Resolution	0.01 unit
	Accuracy	\pm 0.01% of full scale or \pm 0.03 pH units (System accuracy - instrument, sensor, cable: \pm 0.2 pH units)
mV	Range	-1999 to +1999 mV
	Resolution	1 mV
	Accuracy	<u>+</u> 0.1% <u>+</u> 1 digit

EcoSense pH100M Additional Specifications

Operating range	Temperature 0 to 50°C (32 to 122°F)		
	Relative Humidity up to 95%		
Waterproof rating	IP-67 waterproof		
Handheld Size	78 mm wide (widest point) x 184 mm long x 37 mm deep (3.1 in x 7.25 in x 1.45 in)		
Weight with battery	280 grams (0.6 lb)		
ATC Probe	Thermistor, 10kΩ/25°C		
Battery	One 9 volt (included); 150 hour battery life; Real Time Clock (RTC) powered by non-replaceable CR2032 coin battery (3V)		
pH Temperature Comp	ensation Auto/Manual -10.0°C to 120.0°C (14 to 248°F)		
pH Buffer Recognition	US (4.00, 7.00 & 10.0 at 25°C or 4.00, 7.02 & 10.06 at 20°C) or NIST (4.01, 6.86, 9.18 at 25°C or 4.00, 6.87 & 9.23 at 20°C)		
pH Calibration Temper	ature 0°C to 60 °C (32 to 140°F)		
pH Offset Recognition	+90 mV at pH 7.00 or 6.86		
pH Slope Recognition	+30% at pH 4.00, 4.01, 9.18, or 10.01		
Audio Feedback	Yes, all keys		
Autolock feature	Yes		
Auto shutoff	Automatically powers off after 30 minutes of inactivity		
Memory (data sets)	250 (1 data set = pH, temperature, date/time)		
Re-calibration Timer	User-selectable; from 0 to 60 days		
Real-Time Clock (RTC)	Yes, for date/time stamp of saved data and re-calibration timer		
USB Port	Yes, built-in waterproof micro-USB for downloading data to a PC. No software required. USB cable included with instrument		
EcoSense pH100M Ordering Information (order items separately or as a kit)			
601031	pH100M, meter only - includes manual, USB cable and 9 volt battery		
601032	H100M meter, 1 meter cable/probe assembly, carrying case		
601033	100M meter, 4 meter cable/probe assembly, carrying case		
605377	ter waterproof field cable with combo pH electrode and temperature		
605378	r waterproof field cable with combo pH electrode and temperature		
605374 605080	r pH laboratory grade cable and electrode r pH piercing tipped, double-junction cable and electrode		
605081	1-meter pH flat tipped, double junction cable and electrode		
605376	1-meter ORP laboratory grade cable and electrode		
605375	er temperature cable and probe		
606031	sided, plastic carrying case with form fitted foam insert; 31.75 x 22.86 x 9.4 cm (12.5 x 9 x 3.7 in)		
605380	7, 10 electrode simulator (ensures instrument performance)		
603824	pH Buffers; Assorted case of 2 pints each of 4, 7 and 10		



YSI Incorporated

Yellow Springs, OH 45387

1725 Brannum Lane

info@ysi.com

1.800.897.4151

C



a **xylem** brand

2221 (22)

VSI

Specifications are subject to change. Please visit YSI.com to verify all specs. **YSI and EcoSense** are registered trademarks © 2018 YSI, a Xylem brand W133-01 0718