

## YSI Pro20i

PORTABLE DISSOLVED OXYGEN METER



## **Dissolved Oxygen and Temperature Meter**

The **YSI Pro20i** dissolved oxygen (DO) meter is a rugged, user-friendly instrument with a built-in (i.e. integrated) cable for dissolved oxygen and temperature measurements. Choose between galvanic and polarographic DO sensors.

In addition to its impact-resistant, waterproof case, the Pro20i has features that make field sampling faster and easier:



User-replaceable cables and sensors



One Touch Cal for DO calibrations within 3 seconds



Quick response times



| Pro20i System Specifications (Instrument, Probe, and Cable) |                                 |  |
|---|---------------------------------|--|
| Temperature °C, °F  | Range<br>Resolution<br>Accuracy | 23 to 131°F (-5 to 55°C)<br>0 to 45°C for D0 compensation for mg/L<br>0.1°F ( $0.1$ °C)<br>$\pm 0.6$ °F ( $\pm 0.3$ °C)  |
| Dissolved Oxygen<br>% Saturation, % Location                | Range<br>Resolution<br>Accuracy | 0 to 500% 0.1% or 1% air saturation (user selectable) 0 to 200% air saturation, ±2% of the reading or ±2% air saturation, whichever is greater; 200 to 500% air saturation, ±6% of the reading |
| Dissolved Oxygen<br>mg/L, ppm                               | Range<br>Resolution<br>Accuracy | 0 to 50 mg/L 0.01 or 0.1 mg/L (user selectable) 0 to 20 mg/L, $\pm 2\%$ of the reading or $\pm 0.2$ mg/L, whichever is greater; 20 to 50 mg/L, $\pm 6\%$ of the reading                        |
| Barometer<br>mmHg, mbar, inHg, psi, kPa                     | Range<br>Resolution<br>Accuracy | 400 to 999.9 mmHg 0.1 mmHg ±5 mmHg within ±5°C temperature range from calibration point  |

| Pro20i Additional Specifications |  |  |
|----------------------------------|--|--|
| Size                             | 8.3 cm width x 21.6 cm length x 5.6 cm depth<br>(3.25 in. x 8.5 in. x 2.2 in.)   |  |
| Weight with Batteries            | 475 grams (1.05 lbs.)  |  |
| Power                            | 2 alkaline C-cells providing ~400 hours of battery life (without backlight); low battery indicator when 1 hour is left |  |
| Cables                           | 1- 4- 10-m lengths (3.28, 13.1, 32.8 ft.)  |  |
| Salinity Input Range             | 0-70 ppt; manual (automatically compensates for manual input value)  |  |
| Warranty                         | 3-year instrument; 2-year cable; 1-year polarographic sensors; 6-month galvanic sensors                                |  |
| Data Memory                      | 50 data sets   |  |
| Languages                        | English, Spanish, German, French   |  |
| Certifications                   | RoHS, CE, WEEE, IP-67 waterproof, 1-meter drop test  |  |
| Country of Origin                | Assembled in the USA   |  |



YSI, a Xylem brand 1725 Brannum Lane Yellow Springs, OH 45387

**(** +1.937.767.7241



info@ysi.com













YSI.com/Pro20i