

Soil Vapour Implants & Accessories

Surface Connections



1) Red Push on Plastic Cap.



2) Brass Sealing plug with Push-on fitting. No tools required. Dust cap included.



3) Swagelok cap to fit a Summa Cannister. In brass or stainless.



4) 1/8" BSP Male to connect to your own fitting.

Other top fittings readily supplied to specification

Other Items



Teflon tubing:
FEP 1/4" OD, 15m
or 60m rolls.

See Page 2 for Soil Vapour Implant options



Mini Nondo Well Cover:
Small cover ideal for soil vapour installations. Only 150mm OD, 124mm ID, 150mm cast iron skirt, Flush mount, bolt down lid, oring sealed.

Soil Vapour Implants and Weights



SVIFTSWSS: Stainless SVIFTS-6: Stainless steel mesh implant. 150mm steel weight, 22mm long screen with barb connector at top. SVIFTSWSS

Weight stainless steel (screw on) shown below.



SVPT97-6: Stainless steel mesh implant, reverse thread, 150mm long screen with barb connector at top. SVPT97B brass weight (screw on) shown below for use with Geoprobe® rods.
SVPT97B: Brass weight, reverse thread, 20mm.

Do I need a weight?

Due to the coiled teflon tube acting like a spring, it can catch on the sides of the bore. For shallow installations of a few metres, a weight may not be necessary. For deeper installations, a weight is required to pull the implant down to the bottom.

Ordering Information:

EC873301	Redpushon cap
SVK1B	Sealing cap with push on fitting, dust cap included
R2003-0402	1/8" male thread push on fitting
SLB400C	Swagelok fitting for direct connection to Summa Cannister
TT33-15	Teflon tubing, 1/4" OD, 15m long, clear (or TT33.7-60 for 60m roll)
Nondo Mini	Mini Nondo well cover, cast iron, bolt down lid, flush mount, 150mm OD
SVIFTS-6	Soil vapour implant, 150mm screened mesh, stainless steel, with 1/4" barb (or SVPT95-6: reverse threaded for GeoprobeR tooling)
SVIF TSWSS	Stainless Steel weight for SVIFTS-6 soil vapour implant, 22mm
SVPT97B	Brass weight for SVPT95-6 Geoprobe style implant, 22mm, reverse thread